

**FIG. 1**






FIG. 2




| Hex | Dec |            |    |   |
|-----|-----|------------|----|---|
| 0   | 0   | Ethernet   | 01 | Target Ethernet Address                       |
| 1   | 1   | Header     | 02 | (6 bytes)                                     |
| 2   | 2   | (14 bytes) | 03 |   |
| 3   | 3   |            | 04 |   |
| 4   | 4   |            | 05 |   |
| 5   | 5   |            | 06 |   |
| 6   | 6   |            | 07 | Source Ethernet Address                       |
| 7   | 7   |            | 08 | (6 bytes)                                     |
| 8   | 8   |            | 09 |   |
| 9   | 9   |            | 0a |   |
| a   | 10  |            | 0b |   |
| b   | 11  |            | 0c |   |
| c   | 12  |            | 08 | Protocol Type (0x0800=IP)                     |
| d   | 13  |            | 00 |   |
| e   | 14  | IP         | 45 | Version=4, IP Header Len (Words)=5            |
| f   | 15  | Header     | 00 | Service Type                                  |
| 10  | 16  | (20 bytes) | 00 | Total Length=0x001d(29 bytes:20 byte IPHeader |
| 11  | 17  |            | 1d | plus 8-byte UDP header plus 1-byte user data  |
| 12  | 18  |            | eo | Datagram Id=0xe0a1                            |
| 13  | 19  |            | a1 |   |
| 14  | 20  |            | 40 | Flag 0x4 DO NOT FRAGMENT                      |
| 15  | 21  |            | 00 | Fragment Offset=0x000                         |
| 16  | 22  |            | 40 | Time-to-Live=0x40                             |
| 17  | 23  |            | 11 | IP Protocol=0x11(UDP)                         |
| 18  | 24  |            | da | IP Header Checksum=0xda1b                     |
| 19  | 25  |            | 1b |   |
| 1a  | 26  |            | 80 | IP Address of Source=128.1.192.7              |
| 1b  | 27  |            | 01 |   |
| 1c  | 28  |            | c0 |   |
| 1d  | 29  |            | 07 |   |
| 1e  | 30  |            | 80 | IP Address of Destination=128.1.192.8         |
| 1f  | 31  |            | 01 |   |
| 20  | 32  |            | c0 |   |
| 21  | 33  |            | 08 |   |
| 22  | 34  | UDP        | 00 | Source Port=0x0007 (echo datagram)            |
| 23  | 35  | Header     | 07 |   |
| 24  | 36  | (8 bytes)  | 30 | Destination Port=0x3018                       |
| 25  | 37  |            | 18 |   |
| 26  | 38  |            | 00 | UDP Length=0x0009 (8-byte UDP Header plus     |
| 27  | 39  |            | 09 | 1-byte user data)                             |
| 28  | 40  |            | 0c | UDP Checksum=0x0cf8                           |
| 29  | 41  |            | f8 |   |
| 2a  | 42  | User       | 67 | 1 byte user datagram="g"                      |
|     |     | Data       |    |   |
|     |     | (Variable) |    |   |

FIG. 3





**FIG. 6**



**FIG. 7**




FIG. 8





FIG. 9




Replacement Drawing  
Serial No.: 09/686,123  
Inventor: Gernert et al.  
Docket No.: SYM-0606C  
Page 8 of 10

Filed: October 10, 2000  
Title: Communication in a Wireless Communications Network when a Mobile Computer...  
Attorney: William P. Wilbar  
Sierra Patent Group, Ltd.



**FIG. 10A**




**FIG. 10B**






Replacement Drawing  
Serial No.: 09/686,123  
Inventor: Gernert et al.  
Docket No.: SYM-0606C  
Page 9 of 10


Filed: October 10, 2000  
Title: Communication in a Wireless Communications Network when a Mobile Computer...  
Attorney: William P. Wilbar  
Sierra Patent Group, Ltd.



**FIG. 10C**



**FIG. 11**



**FIG. 12**